

4

3

2

1

PART NO. SEE TABLE1

REVISIONS			
LTR	DESCRIPTION	Drawing	DATE
B	RELEASE NEW PRODUCT	GARY	01/16/07
C	修改圖面與實物相符	GARY	02/28/07
D	修改塑膠壁厚	GARY	09/21/07

**CUSTOMER  
DRAWING**

TABLE

020-01-00251	15 U" GOLD	PBT BLACK
020-01-00252	GOLD FLASH	PBT BLACK
020-01-00253	15 U" GOLD	PA BLACK
020-01-00254	GOLD FLASH	PA BLACK
PART NO.	PLATED	COLOR FOR THE PLASTIC

NOTE:

1.MATERIAL :

HOUSING : HIGH TEMPERATURE THERMOPLASTIC ,UL94V-0  
 TERMINAL(MAX): COPPER ALLOY,THICKNESS = 0.30 mm  
 TERMINAL(MIN): COPPER ALLOY,THICKNESS = 0.25 mm

2.PLATING:

CONTACT:GOLD OVER 50u" MIN NICKEL UNDERPLATE  
 SOLDER TAIL: 150u"MIN MISTY TIN 50u" MIN NICKEL UNDERPLATE  
 GOLD SPECIFICATION:SEE TABLE 1

3.ELECTRONICAL SPECIFICATION:

CURRENT RATING: 1.5 AMPERE PER CONTACT  
 CONTACT RESISTANCE: 30 MILLIOHMS MAX.  
 INSULATION RESISTANCE: 1000 MEGOHMS MIN.  
 DIELECTRIC WITHSTANDING VOLTAGE: 500 VDC.  
 OPERATING TEMPERATURE: -40°C~+85°C

4.MEETS THE REQUIREMENTS OF DIRECTIVE 2002/95/EC  
 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL OF 27  
 JANUARY 2003 ON THE RESTRICTION OF THE USE OF CERTAIN  
 HAZARDOUS SUBSTANCES IN ELECTRICAL AND ELECTRONIC  
 EQUIPMENT(ROHS)

DIMENSION ARE MILLIMETERS TOLERANCES ARE : DECIMALS .X ± 0.20 .XX ± 0.15 ANGLE: X ± 3°	APPROVALS		DATE	PART NO. 020-01-00251/00252 020-01-00253/00254
	DRAWN	GARY	09/21/07	
	CHECKED			
	APPROVALS			
TITLE: SAS 29P Vertical 2 ROWS For Cable (SOLDER TAIL 3 IN 1,WITHOUT BULGE)				
SIZE	SCALE :	DRAWING NO.	REV.	
mm	1 : 1	000445	D	
D. NO.	XXXXXXXXXX		SHEET 1 OF 1	

DESCRIPTION

4

3

2

1

NO

Q'TY

UNIT

DO NOT SCALE DRAWING

D. NO.

SHEET 1 OF 1