

4 3 2 1

PART NO.	SEE TABLE1
----------	------------

REVISIONS			
LTR	DESCRIPTION	Drawing	DATE
B	RELEASE NEW PRODUCT	GARY	01/16/07
C	修改圖面與實物相符	GARY	02/28/07

CUSTOMER DRAWING

TABLE

020-01-00255	15 U" GOLD	PBT BLACK
020-01-00256	GOLD FLASH	PBT BLACK
020-01-00257	15 U" GOLD	PA BLACK
020-01-00258	GOLD FLASH	PA BLACK
PART NO.	PLATED	COLOR FOR THE PLASTIC

NOTE:

- MATERIAL :
HOUSING : HIGH TEMPERATURE THERMOPLASTIC ,UL94V-0
TERMINAL(MAX): COPPER ALLOY,THICKNESS = 0.30 mm
TERMINAL(MIN): COPPER ALLOY,THICKNESS = 0.25 mm
- PLATING:
CONTACT:GOLD OVER 50u" MIN NICKEL UNDERPLATE
SOLDER TAIL: 150u"MIN MISTY TIN 50u" MIN NICKEL UNDERPLATE
GOLD SPECIFICATION:SEE TABLE 1
- ELECTRONICAL SPECIFICATION:
CURRENT RATING: 1.5 AMPERE PER CONTACT
CONTACT RESISTANCE: 30 MILLIOHMS MAX.
INSULATION RESISTANCE: 1000 MEGOHMS MIN.
DIELECTRIC WITHSTANDING VOLTAGE: 500 VDC.
OPERATING TEMPERATURE: -40°C~+85°C
- MEETS THE REQUIREMENTS OF DIRECTIVE 2002/95/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL OF 27 JANUARY 2003 ON THE RESTRICTION OF THE USE OF CERTAIN HAZARDOUS SUBSTANCES IN ELECTRICAL AND ELECTRONIC EQUIPMENT(ROHS)

DIMENSION ARE MILLIMETERS TOLERANCES ARE : DECIMALS .X ± 0.30 .XX ± 0.25 ANGLE: X ± 3°	APPROVALS		DATE	PART NO.
	DRAWN	GARY	02/28/07	020-01-00255/00256 020-01-00257/00258
	CHECKED			TITLE: SAS 29P Vertical 2 ROWS R/A For Cable (SOLDER TAIL 3 IN 1,WITHOUT BULGE)
	APPROVALS			SIZE SCALE : mm 1 : 1
				DRAWING NO. 000446
				REV. C
NO	DESCRIPTION	Q'TY	UNIT	DO NOT SCALE DRAWING
4	3	2	1	D NO. XXXXXXXXX SHEET 1 OF 1