

4 3 2 1

PART NO. SEE TABLE 1

REVISIONS			
LTR	DESCRIPTION	Drawing	DATE
B	RELEASE NEW PRODUCT	GARY	01/20/07
C	修改圖面與實物相符	GARY	02/28/07
D	新增剖視圖	GARY	03/20/07
E	修改PCBLAYOUT	GARY	09/24/07

CUSTOMER DRAWING

TABLE

020-01-00259	15 U" GOLD	PA9T BLACK
020-01-00260	GOLD FLASH	PA9T BLACK
020-01-00261	15 U" GOLD	LCP BLACK
020-01-00262	GOLD FLASH	LCP BLACK
PART NO.	PLATED	COLOR AND MATERIAL FOR THE PLASTIC

NOTE:

- MATERIAL :
 BASE: HIGH TEMPERATURE THERMOPLASTIC ,
 UL94V-0, COLOR : SEE TABLE
 TERMINAL(max): PHOSPHOR BRONZE,C5191-EH
 THICKNESS = 0.30 mm
 TERMINAL(min): PHOSPHOR BRONZE,C5191-EH
 THICKNESS = 0.25 mm
- PLATING:
 CONTACT:GOLD OVER 50u" MIN NICKEL UNDERPLATE
 SOLDER TAIL: 150u"MIN MISTY TIN 50u" MIN NICKEL UNDERPLATE
 GOLD SPECIFICATION:SEE TABLE
- ELECTRONICAL SPECIFICATION:
 CURRENT RATING: 1.5 AMPERE PER CONTACT
 CONTACT RESISTANCE: 30 MILLIOHMS MAX.
 INSULATION RESISTANCE: 1000 MEGOHMS MIN.
 DIELECTRIC WITHSTANDING VOLTAGE: 500 VDC.
 OPERATING TEMPERATURE: -40°C~+85°C
- MEETS THE REQUIREMENTS OF DIRECTIVE 2002/95/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL OF 27 JANUARY 2003 ON THE RESTRICTION OF THE USE OF CERTAIN HAZARDOUS SUBSTANCES IN ELECTRICAL AND ELECTRONIC EQUIPMENT(ROHS)

SECTION A-A

PCB LAYOUT T=1.60mm

DIMENSION ARE MILLIMETERS TOLERANCES ARE : DECIMALS .X ± 0.20 .XX ± 0.15 ANGLE: X ± 3°	APPROVALS		DATE	PART NO. 020-01-00259/00260 020-01-00261/00262			
	DRAWN	GARY	09/24/07				
	CHECKED			TITLE: SAS 29P SOCKET (Edge mount , Without BULGE)			
	APPROVALS			SIZE SCALE : mm 1 : 1 DRAWING NO. 000449 REV. E			
NO	DESCRIPTION	QTY	UNIT	DO NOT SCALE DRAWING	ID NO.	XXXXXXXXXX	SHEET 1 OF 1

4 3 2 1