

4

3

2

1

PART NO. SEE TABLE1

REVISIONS			
LTR	DESCRIPTION	Drawing	DATE
B	RELEASE NEW PRODUCT	GARY	05/24/07
C	修改圖面與實物相符	GARY	06/15/07
D	增加凸點	GARY	06/30/07
E	加高小7PIN	GARY	07/24/07
F	修改塑膠壁厚及變更GP料號	GARY	10/18/07

CUSTOMER DRAWING

TABLE 1

020-01-00289	15 U" GOLD	PBT BLACK	GP
020-01-00290	15 U" GOLD	PA9T BLACK	ROHS
PART NO.	PLATED	COLOR FOR THE PLASTIC	NOTE

NOTE:

1.MATERIAL :

BASE: PA9T&PBT , G.F.30%, UL94V-0,

TERMINAL(max): PHOSPHOR BRONZE,C5191-H
THICKNESS = 0.30 mmTERMINAL(3 IN 1): PHOSPHOR BRONZE,C5210-EH
THICKNESS = 0.30 mmTERMINAL(min): PHOSPHOR BRONZE,C5210-EH
THICKNESS = 0.25 mm

2.PLATING:

CONTACT:GOLD OVER 50u" MIN NICKEL UNDERPLATE

SOLDER TAIL: 150u"MIN MISTY TIN 50u" MIN NICKEL UNDERPLATE
GOLD SPECIFICATION:SEE TABLE 1

3.ELECTRONICAL SPECIFICATION:

CURRENT RATING: 1.5 AMPERE PER CONTACT

CONTACT RESISTANCE: 30 MILLIOHMS MAX.

INSULATION RESISTANCE: 1000 MEGOHMS MIN.

DIELECTRIC WITHSTANDING VOLTAGE: 500 VDC.

OPERATING TEMPERATURE: -40°C~+85°C

4.MEETS THE REQUIREMENTS OF DIRECTIVE 2002/95/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL OF 27 JANUARY 2003 ON THE RESTRICTION OF THE USE OF CERTAIN HAZARDOUS SUBSTANCES IN ELECTRICAL AND ELECTRONIC EQUIPMENT(ROHS)

SECTION A-A SECTION B-B

SECTION C-C

DIMENSION ARE MILLIMETERS		APPROVALS		DATE
TOLERANCES ARE :		DRAWN	GARY	10/18/07
DECIMALS		CHECKED		
X ± 0.20		APPROVALS		
.XX ± 0.15				
ANGLE:				
X ± 3'				
		SIZE	SCALE :	DRAWING NO.
		mm	1 : 1	000489
				REV. F
		D NO.	XXXXXXXXXX	SHEET 1 OF 1

DESCRIPTION

NO

4

3

2

1