

4

3

2

1

PART NO. SEE TABLE1

REVISIONS			
LTR	DESCRIPTION	Drawing	DATE
A	新發行圖面	GARY	08/16/07
B	修改塑膠壁厚	GARY	09/21/07

CUSTOMER DRAWING

TABLE

020-01-00310	15 U" GOLD	PA BLACK
020-01-00311	15 U" GOLD	PBT BLACK
PART NO.	PLATED	COLOR FOR THE PLASTIC

NOTE:

1.MATERIAL :

HOUSING : HIGH TEMPERATURE THERMOPLASTIC ,UL94V-0

TERMINAL(MAX): COPPER ALLOY,THICKNESS = 0.30 mm

TERMINAL(MIN): COPPER ALLOY,THICKNESS = 0.25 mm

2.PLATING:

CONTACT:GOLD OVER 50u" MIN NICKEL UNDERPLATE

SOLDER TAIL: 150u"MIN MISTY TIN 50u" MIN NICKEL UNDERPLATE

GOLD SPECIFICATION:SEE TABLE 1

3.ELECTRONICAL SPECIFICATION:

CURRENT RATING: 1.5 AMPERE PER CONTACT

CONTACT RESISTANCE: 30 MILLIOHMS MAX.

INSULATION RESISTANCE: 1000 MEGOHMS MIN.

DIELECTRIC WITHSTANDING VOLTAGE: 500 VDC.

OPERATING TEMPERATURE: -40°C~+85°C

4.MEETS THE REQUIREMENTS OF DIRECTIVE 2002/95/EC

OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL OF 27

JANUARY 2003 ON THE RESTRICTION OF THE USE OF CERTAIN

HAZARDOUS SUBSTANCES IN ELECTRICAL AND ELECTRONIC

EQUIPMENT(ROHS)

DIMENSION ARE MILLIMETERS TOLERANCES ARE : DECIMALS .X ± 0.20 .XX ± 0.15 ANGLE: X ± 3°	APPROVALS		DATE	PART NO.
	DRAWN	GARY	09/24/07	020-01-00310/00311
	CHECKED			TITLE:
	APPROVALS			SAS29PIN線式，端子三連PIN 有特殊PIN，無凸點
	SIZE	SCALE :	DRAWING NO.	REV.
	mm	1 : 1	000518	B
NO	DESCRIPTION	Q'TY	UNIT	DO NOT SCALE DRAWING
D. NO.	XXXXXXXXXX	SHEET 1 OF 1		

4

3

2

1