

4

3

2

1

PART NO. SEE TABLE1

REVISIONS			
LTR	DESCRIPTION	Drawing	DATE
A	新產品發行圖面	GARY	03/28/08
B	增加無螺絲孔料號	GARY	03/16/09
C	新增料號	Jun.L	06/04/09

CUSTOMER DRAWING

TABLE 1

54.40	48.00	020-01-00421	15 U"	PBT BLACK	GP	有螺絲孔
58.40	52.00	020-01-00404	30 U"	LCP BLACK	GP	無螺絲孔
		020-01-00403	30 U"	PBT BLACK	GP	無螺絲孔
		020-01-00402	15 U"	LCP BLACK	GP	無螺絲孔
		020-01-00401	15 U"	PBT BLACK	GP	無螺絲孔
		020-01-00339	30 U"	LCP BLACK	GP	有螺絲孔
		020-01-00340	30 U"	PBT BLACK	GP	有螺絲孔
		020-01-00341	15 U"	LCP BLACK	GP	有螺絲孔
020-01-00342	15 U"	PBT BLACK	GP	有螺絲孔		
DIM=A	DIM=B	PART NO.	CONTACT	MATERIAL & COLOR	NOTE	NOTE 2

SECTION A-A

NOTE:

- MATERIAL :
HOUSING : HIGH TEMPERATURE THERMOPLASTIC ,UL94V-0
TERMINAL(MAX): COPPER ALLOY,THICKNESS = 0.30 mm
TERMINAL(MIN): COPPER ALLOY,THICKNESS = 0.25 mm
- PLATING:
CONTACT:GOLD OVER 50u" MIN NICKEL UNDERPLATE
SOLDER TAIL: 150u"MIN MISTY TIN 50u" MIN NICKEL UNDERPLATE
GOLD SPECIFICATION:SEE TABLE 1
- ELECTRONICAL SPECIFICATION:
CURRENT RATING: 1.5 AMPERE PER CONTACT
CONTACT RESISTANCE: 30 MILLIOHMS MAX.
INSULATION RESISTANCE: 1000 MEGOHMS MIN.
DIELECTRIC WITHSTANDING VOLTAGE: 500 VAC.
OPERATING TEMPERATURE: -40°C~+85°C

DIMENSION ARE MILLIMETERS TOLERANCES ARE : DECIMALS .X ± 0.30 .XX ± 0.25 ANGLE: X ± 3°	APPROVALS		DATE	TITLE: SAS 29P SOCKET 加長帶螺絲孔型		
	DRAWN	Jun.L	06/04/09			
	CHECKED			SIZE SCALE : mm 1 : 1 DRAWING NO. 000582 REV. C		
	APPROVALS					
D NO.		XXXXXXXXXX	SHEET 1 OF 1			

NO DESCRIPTION Q'TY UNIT DO NOT SCALE DRAWING

4

3

2

1