

4 3 2 1

CUSTOMER DRAWING

PART NO. SEE TABLE

REVISIONS			
LTR	DESCRIPTION	Drawing	DATE
B	新版發行	Jun.L	04/28'/08

料號	端子電鍍	塑膠材質
020-01-00353	15u"	PBT
020-01-00354	30u"	PBT
020-01-00359	15u"	LCP
020-01-00360	30u"	LCP

RECOMMENDED PCB LAYOUT

NOTE: THICKNESS=2.4mm

1.MATERIAL :
 HOUSING:High Temperature Thermoplastic,UL94V-0,COLOR:BLACK
 TERMINAL(max): Copper Alloy,THICKNESS=0.30mm
 TERMINAL(min): Copper Alloy,THICKNESS=0.30mm
 LATCH:SUS,THICK=0.30±0.01

2,PLATING:
 CONTACT: Au OVER 50u" MIN NICKEL UNDERPLATE
 SOLDER TAIL: 100u"MIN MISTY TIN 50u" MIN NICKEL UNDERPLATE

3.ELECTRONICAL SPECIFICATION:
 CURRENT RATING: 1.5 AMPERE PER CONTACT
 CONTACT RESISTANCE: 30 MILLIOHMS MAX.
 INSULATION RESISTANCE: 1000 MEGOHMS MIN.
 DIELECTRIC WITHSTANDING VOLTAGE: 500 VAC.
 OPERATING TEMPERATURE: -20°C~+85°C

SECTION A-A

DESCRIPTION

DIMENSION ARE MILLIMETERS		APPROVALS		DATE
TOLERANCES ARE :	DRAWN	Jun.L	04/28'/08	
DECIMALS	CHECKED			
.X ± 0.30	APPROVALS			
.XX ± 0.25				
ANGLE:				
X ± 3'				

TITLE: SAS 29P 母頭魚眼孔加高型(W=2.7+2.1)			
SIZE	SCALE :	DRAWING NO.	REV.
mm	1 : 1	000594	B
ID NO.	XXXXXXXXXX	SHEET 1 OF 1	

NO QTY UNIT DO NOT SCALE DRAWING

4 3 2 1