




Mating Height Drawing



2P;3P



Specifications:


Current rating:1.0A AC,DC  
 Voltage rating:125V AC,DC  
 Contact resistance:20m ohm.Max  
 Insulation resistance:100M ohm.Min  
 Withstanding voltage:250V AC/minute  
 Operating temperature range:-40°C~+85°C  
 Material:

Insulator:High Temp. Plastic(Nylon 46 UL94V-0)  
 Insulator Color:White  
 Contact:Phosphor Bronze  
 Plated:Tin Plated

How To Order:

1251R-XX-SM1

- SMD Type
- No.Of Position
- Right Angle Type



PCB LAYOUT

Dimension:

Pos	DimA	DimB	DimC	Pos	DimA	DimB	DimC
2	1.25	7.25	4.25	9	10.00	16.00	13.00
3	2.50	8.50	5.50	10	11.25	17.25	14.25
4	3.75	9.75	6.75	11	12.50	18.50	15.50
5	5.00	11.00	8.00	12	13.75	19.75	16.75
6	6.25	12.25	9.25	13	15.00	21.00	18.00
7	7.50	13.50	10.50	14	16.25	22.25	19.25
8	8.75	14.75	11.75	15	17.50	23.50	20.50

RoHS Compliant

				DRAWN: DXS	GENERAL TOLERANCE: .X=±0.2 .XX=±0.15		
				CHECKED: Jeremy Liu	UNIT: MM	DESCRIPTION:	SIZE
C	05-Sep-2008	ECN-CN080910	Andrew		SCALE:1:1	1.25mm Wafer Right Angle SMD Type	<b>A4</b>
B	10-May-2006	ECN-CN060510	Jin Taihua	APPROVAL: Mike Wu	SHEET: 1 / 1	PART NO:	
A	08-Feb-2006	(PC0001)	DXS		PROJECTION:	1251R-XX-SM1	
REV	DATE	FILE	BY				