



REV	MODIFICATION	DATE	DRAW
B	EN-06-1125	95/11/27	TERENCE

Specification:

- * Withstanding Voltage: 500V DC /1M.
- * Insulation Resistance: 1000M Ohm
- * Voltage Rating: 5V AC
- * Current Rating: 0.5A/Product Max.
- * Contact Resistance: 60m Ohm Max.
- * Operating Temperature: -25°C ~ +85°C
- * Insertion Cycles: 10000 Times Min
- * Press Force: 0.2N~0.6N

Material and Finish:

- * Housing: LCP+30%G.F. UL 94V-0, Black
- * Contact: Copper Alloy
- * Contact Area: Gold Plating All Over Ni

ORDER INFORMATION:

SIMMP-P XX XX BT X 0

NO. OF CONTACTS: 06: 6PIN, 08: 8PIN

Packing: 0: Tube, R: Tape & Reel

Plating: 10: 10u", 30: 30u"

DIMENSION IN mm [Inch]		PRD. SPEC.		ALMITA CO., LTD.	
TOLERANCE UNLESS OTHERWISE SPECIFIED		PKG. SPEC.			
.X±0.30	X.*±	APPROVE		SIM CARD CONN. PUSH-IN/OUT SMT TYPE	
.XX±0.20	.X.*±	CHECK		FILE NO. SIM-KF016	DWG NO. SIMMP-PXXXXBTX0
.XXX±0.10	.XX.*±	DRAW		SIZE A4	PROJ. SHEET 1 / 1
				SCALE 2:1	REV B