



| Pin Type | DIM.L | Pin Type | REV | MODIFICATION | DATE | DRAW |
|----------|---------|----------------|-----|--------------|-----------|------|
| Detect | 3.5 mm | 25,26 | B | EN-06-0935 | 9/25/2006 | TONY |
| General | 4.25 mm | All Other Pins | | | | |
| Power | 5.0 mm | 1,13,38,50 | | | | |

SPECIFICATIONS:
 HOUSING : High Temperature Plastic, UL 94V-0
 CONTACT : Copper Alloys
 VOLTAGE RATING : 100VAC
 CURRENT RATING : 0.5A
 CONTACT RESISTANCE:40 m Ohm max.
 INSULATION RESISTANCE:1000M Ohm min.
 DIELECTRIC STRENGTH : 500VAC/1min
 OPERATION TEMPERATURE : -40°C~85°C

Ordering Information:
 CFC M D - 1 5 X XX W 00 0
 Pin No. 50 Position
 Color: W-White.
 TYPE 1
 0 : TIN/LEAD 90/10
 T : LEAD FREE TIN 100%
 Contact Area Plating:
 15--15U" Gold Plating.
 30--30U" Gold Plating.

| DIMENSION IN mm [Inch] | | PROD. SPEC. |
|--------------------------------------|--------------|------------------------|
| TOLERANCE UNLESS OTHERWISE SPECIFIED | | SP0011 |
| .X±0.30 | X.*± 1* | PKG. SPEC. PPP-CFC-001 |
| .XX±0.20 | .X.*± 0.5* | APPROVE |
| .XXX±0.10 | .XX.*± 0.25* | CHECK |
| | | DRAW |

| | | |
|------------------|--|--------------------|
| ALMITA CO., LTD. | | |
| TITLE | 1.27mm CF CARD CONN. 50PIN TYPE1 NORMAL TYPE | CUSTOMER DRAWING |
| FILE NO. KFP-011 | DWG NO. CFCMD-15XXXW000 | |
| SIZE | A4 | PROJ. SHEET 1 / 1 |
| | SCALE 1:1 | REV B |