



Pin Type	Interface Dim L	Pin Type	REV	MODIFICATION	DATE	DRAW
Detect	3.5 mm	25,26				
General	4.25 mm	All Other Pins				
Power	5.0 mm	1,13,38,50				

SPECIFICATIONS:

HOUSING : High Temperature Plastic, UL 94V-0
 CONTACT : Copper Alloys
 VOLTAGE RATING : 100VAC
 CURRENT RATING : 0.5A
 CONTACT RESISTANCE:40 mΩ max.
 INSULATION RESISTANCE:1000M Ω max.
 DIELECTRIC STRENGTH : 500VAC/1min
 OPERATION TEMPERATURE : -40°C~85°C

CFCMC- 6 50 XX B 00 3
 Dim-A
 3-0.80 mm

CF STRADDLE MOUNT(A TYPE)
 Contact Area Plating:
 01-Gold Flash Gold Plating.
 05-5U" Gold Plating.
 15-15U" Gold Plating.

DIMENSION IN mm [Inch]		PROD. SPEC. SPO049	ALMITA CO., LTD.	
TOLERANCE UNLESS OTHERWISE SPECIFIED		PKG. SPEC.	TITLE CF STRADDLE MOUNT (A TYPE)	CUSTOMER DRAWING
.X±0.30	X.*± 1'	APPROVE <i>[Signature]</i>	FILE NO. KFP-049	DWG NO. CFCMC-650XXB003
.XX±0.20	.X.*± 0.5'	CHECK <i>[Signature]</i>	PROJ.	SHEET 1 / 1
.XXX±0.10	.XX.*± 0.25'	DRAW <i>[Signature]</i>	SIZE A4	SCALE 2:1 REV A