



Pin Type	DIM.L	Pin Type	REV	MODIFICATION	DATE	DRAW
Detect	3.5 mm	25,26	B	EN-06-0935	9/25/2006	TONY
General	4.25 mm	All Other Pins				
Power	5.0 mm	1,13,38,50				

SPECIFICATIONS:
 HOUSING : High Temperature Plastic, UL 94V-0
 CONTACT : Copper Alloys
 VOLTAGE RATING : 100VAC
 CURRENT RATING : 0.5A
 CONTACT RESISTANCE:40 m Ohm max.
 INSULATION RESISTANCE:1000M Ohm min.
 DIELECTRIC STRENGTH : 500VAC/1min
 OPERATION TEMPERATURE : -40°C~85°C

Ordering Information:
 CFC M D - 1 5 X XX W 00 1
 Pin No. 50 Position
 Color: W-White.
 TYPE 2
 0 : TIN/LEAD 90/10
 T : LEAD FREE TIN 100%
 Contact Area Plating:
 15--15U" Gold Plating.
 30--30U" Gold Plating.

DIMENSION IN mm [Inch]		PROD. SPEC.
TOLERANCE UNLESS OTHERWISE SPECIFIED		SP0011
.X±0.30	X.*± 1°	PKG. SPEC. PPP-CFC-001
.XX±0.20	.X.*± 0.5°	APPROVE
.XXX±0.10	.XX.*± 0.25°	CHECK
		DRAW

ALMITA CO., LTD.			
TITLE		CUSTOMER DRAWING	
1.27mm CF CARD CONN. 50PIN TYPE1,2 NORMAL TYPE			
FILE NO. KFP-011	DWG NO. CFCMD-15XXXW001		
SIZE A4	PROJ.	SHEET 1 / 1	
	SCALE 1:1	REV B	