



REV	MODIFICATION	DATE	DRAW
B	EN-08-0731	97.07.31	SAN

PIN TYPE	DIM.L±0.10	PIN NUMBER
DETECT	3.50	36,67
GENERAL	4.25	ALL OTHER PINS
POEWR	5.00	1,17,34,35,51,68

FEATURES:  
 \*MATERIAL:  
 1.INSULATOR:UL94V-0 LCP,PBT.  
 2.CONTACT:COPPER ALLOY.  
 \*COLOR:BLACK.  
 \*WITH 4 PCS M2xCmm AND  
 \*ACCEPT PCMCIA TYPE I,  
 TYPE II OR TYPE III CARD.

A \ B	DIMB=1.1mm VOLTAGE 5V	DIMB=2.2mm VOLTAGE 3.3V	DIM "C"
A=5.0mm	050(P/N尾碼三位)	05V(P/N尾碼三位)	13.3
A=8.0mm	080(P/N尾碼三位)	08V(P/N尾碼三位)	16.3
A=15.0mm	150(P/N尾碼三位)	15V(P/N尾碼三位)	23.3

ORDER INFORMATION:  
 PCMLN-06801BXXX- G  
 COMPLY TO RoHS

DIMENSION IN mm [Inch]		PROD. SPEC.	C	
TOLERANCE UNLESS OTHERWISE SPECIFIED		PKG. SPEC.	TITLE PCMCIA ASSEMBLY CUSTOMER DRAWING	
.X±0.20	.X'± 2'	APPROVE <i>Gomy</i>	FILE NO.	DWG NO. PCMLN-06801BXXX-G
.XX±0.10	.X'± 1'	CHECK <i>Tony</i>	SIZE A4	PROJ.  SHEET 1 / 1
.XXX±0.05	.XX'± 0.5'	DRAW <i>San 3/31</i>	SCALE 1:1	REV B