



| REV | MODIFICATION | DATE | DRAW |
|-----|--------------|----------|---------|
| B | EN-06-0616 | 95/06/15 | TERENCE |

| PIN TYPE | DIM.L±0.10 | PIN NUMBER |
|----------|------------|------------------|
| DETECT | 3.50 | 36,67 |
| GENERAL | 4.25 | ALL OTHER PINS |
| POEWR | 5.00 | 1,17,34,35,51,68 |

FEATURES:
 *MATERIAL:
 1.INSULATOR:UL94V-0 LCP,PBT.
 2.CONTACT:COPPER ALLOY.
 *COLOR:BLACK.
 *WITH 4 PCS M2xCmm AND
 *ACCEPT PCMCIA TYPE I,
 TYPE II OR TYPE III CARD.

| A \ B | DIMB=1.1mm VOLTAGE 5V | DIMB=2.2mm VOLTAGE 3.3V | DIM "C" |
|----------|--------------------------|----------------------------|---------|
| A=0.0mm | A=0.0mm:000 | A=0.0mm:00V | 8.3 |
| A=2.2mm | A=2.2mm:022 | A=2.2mm:V22 | 10.3 |
| A=3.0mm | A=3.0mm:030 | A=3.0mm:03V | 11.3 |
| A=4.0mm | A=4.0mm:040 | A=4.0mm:04V | 12.3 |
| A=5.0mm | A=5.0mm:050 | A=5.0mm:05V | 13.3 |
| A=5.5mm | A=5.5mm:055 | A=5.5mm:V55 | 13.3 |
| A=6.0mm | A=6.0mm:060 | A=6.0mm:06V | 14.3 |
| A=7.0mm | A=7.0mm:070 | A=7.0mm:07V | 15.3 |
| A=8.0mm | A=8.0mm:080 | A=8.0mm:08V | 16.3 |
| A=9.0mm | A=9.0mm:090 | A=9.0mm:09V | 17.3 |
| A=10.0mm | A=10.0mm:100 | A=10.0mm:10V | 18.3 |

ORDER INFORMATION:
 PCMLR-0XX XX B XXX
 PIN NO. 30: 30μ"
 01: G/F
 15: 15μ"
 000/00V: A=0.0mm
 022/V22: A=2.2mm
 030/03V: A=3.0mm
 040/04V: A=4.0mm
 050/05V: A=5.0mm
 055/V55: A=5.5mm
 060/06V: A=6.0mm
 070/07V: A=7.0mm
 080/08V: A=8.0mm
 090/09V: A=9.0mm
 100/10V: A=10.0mm

| DIMENSION IN mm [Inch] | | PROD. SPEC. | C | |
|--------------------------------------|-------|-------------|---|-------------------------|
| TOLERANCE UNLESS OTHERWISE SPECIFIED | | PKG. SPEC. | TITLE PCMCIA SINGLE STACK PC CARD PLUG AND LONG RIGHT EJECTOR | |
| .X±0.30 | X*± | APPROVE | CUSTOMER DRAWING | |
| .XX±0.20 | .X*± | CHECK | FILE NO. | DWG NO. PCMLR-0XXXXBXXX |
| .XXX±0.10 | .XX*± | DRAW | SIZE A4 | PROJ. SHEET 1 / 1 |
| | | | SCALE 1:1 | REV B |