

4

3

2

1

PART NO. SEE TABLE

REVISIONS			
LTR	DESCRIPTION	Drawing	DATE
A0	NEW	BILL	10/28/07
B	依客戶要求鐵殼增加LOGO	BILL	06/26/08

CUSTOMER DRAWING

TABLE 1

020-01-00318	15U"	LCP BLACK
020-01-00319	30 U"	LCP BLACK
PART NO.	PLATED	PLASTIC&COLOR

RECOMMENDED PCB LAYOUT

NOTE:

1.MATERIAL :

BASE&COVER: HIGH THERMOPLASTIC UL94V-0, COLOR : BLACK
 TERMINAL: COPPER ALLOY, T= 0.20 mm
 SHELL: STEEL,T= 0.25 mm

2.PLATING:

CONTACT:GOLD PLATED ON THE CONTACT.
 TIN PLATED ON THE SOLDER TAIL.
 NICKEL UNDERPLATED OVER ALL.
 SHELL: NICKEL UNDERPLATED OVER ALL.

3.ELECTRONICAL SPECIFICATION:

CURRENT RATING: 0.5 AMPERE PER CONTACT
 CONTACT RESISTANCE: 20 MILLIOHMS MAX.
 INSULATION RESISTANCE: 1000 MEGOHMS MIN.
 DIELECTRIC WITHSTANDING VOLTAGE: 300 VAC.
 OPERATING TEMPERATURE: -25°C~+85°C

4.THE PRODUCT SHOULD BE GP COMPLIANCE.

SECTION A-A

logo深為0.03mm

DETAIL C

DIMENSION ARE MILLIMETERS TOLERANCES ARE : DECIMALS	APPROVALS		DATE	TITLE:
	DRAWN	BILL	06/26/08	
.X ± 0.20 .XX ± 0.15	CHECKED			SAS 26P SOCKET 180° SMT TYPE
ANGLE: X ± 1°	APPROVALS			
				SIZE mm
				SCALE : 1 : 1
				DRAWING NO. 000540
				REV. B
				ID NO. XXXXXXXXXX
				SHEET 1 OF 1

DESCRIPTION

NO

QTY

UNIT

DO NOT SCALE DRAWING

4

3

2

1