

4 3 2 1

PART NO. SEE TABLE

REVISIONS			
LTR	DESCRIPTION	Drawing	DATE
A0	NEW	BILL	10/27/07
A1	主體過高溫時變形，更改主體結構	BILL	06/10/08
B	依客戶要求鐵殼增加LOGO標示	BILL	06/26/08

CUSTOMER DRAWING

TABLE 1

020-01-00329	15U"	LCP BLACK
020-01-00321	30 U"	LCP BLACK
PART NO.	PLATED	PLASTIC&COLOR

SECTION A-A

ALL CONTACT

logo深為0.03mm
DETAIL B
SCALE 2:1

RECOMMENDED PCB LAYOUT

NOTE:

- MATERIAL :
BASE: HIGH THERMOPLASTIC UL94V-0, COLOR : BLACK
TERMINAL: COPPER ALLOY, T= 0.20 mm
SHELL:STEEL,T=0.25mm.
- PLATING:
CONTACT:GOLD PLATED ON THE CONTACT.
TIN PLATED ON THE SOLDER TAIL.
NICKEL UNDERPLATED OVER ALL.
SHELL:NICKEL UNDERPLATED OVER ALL.
- ELECTRONICAL SPECIFICATION:
CURRENT RATING: 0.5 AMPERE PER CONTACT
CONTACT RESISTANCE: 20 MILLIOHMS MAX.
INSULATION RESISTANCE: 1000 MEGOHMS MIN.
DIELECTRIC WITHSTANDING VOLTAGE: 300 VAC.
OPERATING TEMPERATURE: -25°C~+85°C
- THE PRODUCT SHOULD BE GP COMPLIANCE.

DIMENSION ARE MILLIMETERS TOLERANCES ARE : DECIMALS .X ± 0.20 .XX ± 0.15 ANGLE: X ± 1°	APPROVALS		DATE	TITLE:			
	DRAWN	BILL	06/26/08	SAS 26P 90° SOCKET SMT TYPE			
CHECKED			SIZE	SCALE :	DRAWING NO.	REV.	
APPROVALS			mm	1 : 1	000541	B	
DO NOT SCALE DRAWING	ID NO.	XXXXXXXXXX	SHEET 1 OF 1				

DESCRIPTION

NO 4 3 2 1